

BLANK PAGE



*RE_AFFIRMED 1995**
...IS: 9174 - 1979

DIMENSIONS FOR SINGLE-HOLE MOUNTED LEVER-OPERATED SWITCHES FOR AIRCRAFT

UDC 621·316·542 : 629·13·066 : 006·78



@ Copyright 1979

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002



Indian Standard

DIMENSIONS FOR SINGLE-HOLE MOUNTED LEVER-OPERATED SWITCHES FOR AIRCRAFT

Aircraft Electrical Equipment Sectional Committee, ETDC 55

Chairman

Representing

GP CAPT P. GOPALAN

Aeronautical Development Estt (R & D). Ministry of Defence, Bangalore

Members

WG CDR G. B. SINGH (Alternate to

Gp Capt P. Gopalan) SHRI M. N. ARORA

SHRI M. S. ERBOTE (Alternate)

Indian Airlines Corporation, New Delhi

SHRI H. V. BADRINATH

Wireless Planning and Coordination Wing. Ministry of Communications, New Delhi

National Aeronautical Laboratory (NAL),

SHRI S. BALAKRISHNA

Bangalore Hindustan Aeronautics Ltd, Bangalore

SHRI M. K. BASU

WG CDR H. R. SEETHARAM (Alternate) GP CAPT H. S. BHATIA

Directorate of Technical Development and Production (Air), Ministry of Defence, New Delhi

SHRI H. C. PANDE (Alternate)

Indian Cable Co Ltd, Calcutta

SHRI M. DEY

SHRI K. V. R. RAO (Alternate) SHRI RAM KUMAR GUPTA

Delton Cable Industries Pvt Ltd, Delhi

SHRI P. MUKUNDAN (Alternate) SHRI A. N. GHOSH

Development Commissioner, Small Scale Industries, New Delhi

Shri R. Narasimhan SHRI A. PURSHOTAM

Civil Aviation Department, New Delhi

International Airports Authority

of India.

SHRI K. S. JAYRAM (Alternate) DR VEPA NARAYANA MURTHY

Indian Space Research Organization (Vikram Sarabhai Space Centre), Trivandrum
Directorate General of Technical Development

SHRI K. SANKARANARAYANAN

(DGTD), New Delhi

(Continued on page 2)

© Copyright 1979

New Delhi

INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 9174 - 1979

(Continued from page 1)

Members

Representing

SHRI C. SITAPATI RAO

Electronics Testing & Development Centre,

Hyderabad

SHRI M. N. SOMASUDARAM
SHRI A. I. HYDER (Alternate)

Air India, New Delhi

SHRI A. I. HYDER (Alternate SHRI S. P. SACHDEV,

Director General, ISI (Ex-officio Member)

Director (Elec tech)

Secretaries

SHRI H. C. DUNEJA Assistant Director (Elec tech), ISI

SHRI R. S. SARMA Assistant Director (Elec tech), ISI

Indian Standard DIMENSIONS FOR SINGLE-HOLE MOUNTED LEVER-OPERATED SWITCHES FOR AIRCRAFT

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 18 May 1979, after the draft finalized by the Aircraft Electrical Equipment Sectional Committee had been approved by the Electrotechnical Division Council.
- 0.2 This standard is based on ISO 493-1975 Aircraft Dimensions for single-hole mounting (class 1 and class 2) lever-operated manual switches, issued by the International Organization for Standardization.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies the overall dimensions for two classes of single hole mounting (class 1 and class 2) lever operated switches for use in 28 V dc and 115/200 V ac, 3-phase, 400 Hz systems in aircraft. Class 1 switches are sealed and are suitable for higher altitudes and temperature conditions. Class 2 switches are sealed only at the lever entry.


2. DIMENSIONAL REQUIREMENTS

2.1 The overall dimensions shall be in accordance with Fig. 1, which are suitable for accommodating either terminal screws or integral terminal on the face opposite the mounting bush.

^{*}Rules for rounding off numerical values (revised).

IS: 9174 - 1979

2.2 The switches shall have at the centre of the front face of the case a 12-mm diameter male thread of 1 mm pitch for fixing to the mounting panel. The holes in the mounting panel for fixing the switch to the panel shall be as shown in Fig. 1(B). The smaller hole of diameter 3 mm together with a keyway washer which also locates in a keyway in the switch mounting bush, shall be used to prevent rotation of the switch and shall orientate the switch correctly.



Dimensions		VALUE	
A		48·3 Max	
В	Single-pole Double-pole Three-pole Four-pole	16·8 Max 22·6 Max 35·1 Max 46·0 Max	
\overline{c}		34·3 Max	
D		12.3 Max	
E*		23.8 ± 1.6 20° ± 2°	

All dimensions in millimetres.

FIG. 1 DIMENSIONS FOR SINGLE-HOLE MOUNTING SWITCH